



ELECTRIC WATER HEATERS



- ▶ Capacities from 5 to 120 l.
- ▶ Double anti-corrosion protection: ceramic enamel + magnesium anode.
- ▶ Insulation: polystyrene (5-10) or polyurethane (30-120) foam.
- ▶ Electric heater: 1,5 kW (5-30 l) or 2 kW (50-120 l).
- ▶ Manual temperature regulation.
- ▶ Warranty: 24 months.

Technical specification of the Fox 5-10

specification	unit	Fox			
catalogue number	-	01-005970FOX	01-005070FOX	01-010970FOX	01-010070FOX
EAN	-	5901224218125	5901224218132	5901224218156	5901224218149
type	-	above-basin	below-basin	above-basin	below-basin
storage capacity	l	5	5	10	10
load profile	-	3XS	3XS	XXS	XXS
energy efficiency class	-	B	B	B	B
tank's maximum working pressure	MPa	0,6	0,6	0,6	0,6
voltage	V~	230	230	230	230
electric heater power	kW	1,5	1,5	1,5	1,5
range of working temperatures	°C	30÷65	30÷65	30÷65	30÷65
est. time to warm up the water ($\Delta t=35\text{ }^{\circ}\text{C}$)	min	9	9	18	18
magnesium anode (M8 screw)	mm	22x100	22x100	22x100	22x100
height	mm	385	385	435	435
width	mm	250	250	290	290
depth	mm	215	215	270	270
spacing (cold and hot water couplings)	mm	80	80	80	80
net weight	kg	4,5	4,5	5,5	5,5

Technical specification of the Fox 30-120

specification	unit	Fox				
catalogue number	-	01-030000	01-050000	01-080000	01-100000	01-120000
EAN	-	5901224215353	5901224214776	5901224214783	5901224200991	5901224201165
storage capacity	l	30	50	80	100	120
load profile	-	S	M	M	M	L
energy efficiency class	-	C	C	C	C	C
tank's maximum working pressure	MPa	0,6	0,6	0,6	0,6	0,6
voltage	V~	230	230	230	230	230
electric heater power	kW	1,5	2,0	2,0	2,0	2,0
range of working temperatures	°C	30÷65	30÷65	30÷65	30÷65	30÷65
est. time to warm up the water to 65°C ($\Delta t=55\text{ }^{\circ}\text{C}$)	min	60	90	150	180	200
magnesium anode (M8 screw)	mm	25x200	25x200	25x310	25x310	25x390
height	mm	550	540	790	945	1110
diameter	mm	Ø 360	Ø 440	Ø 440	Ø 440	Ø 440
spacing (cold and hot water couplings)	mm	100	100	100	100	100
hanger's distance from the top of the tank	mm	160	172	172	172	172
distance between hanger's screws	mm	260	260	260	260	260
net weight	kg	15	19	24	30	33



„Galmet Sp. z o.o.” Sp. K.
48-100 Głubczyce, Raciborska 36

tel.: +48 77 403 45 00
fax: +48 77 403 45 99

export dept.: +48 77 403 45 80
export@galmet.com.pl

Distributor